

OE Approved Mobil Coolants

- Mobil Coolants offer OE approvals across PV, CV and Industrial sectors
- The range compliments the Flagship and Premium lubricants product portfolio



Glystantin® is a brand of BASF – We create chemistry



	Antifreeze Extra Coolant Extra	Antifreeze Advanced	Antifreeze Ultra	Antifreeze Heavy Duty	Machine Tool Long Life Coolant	Antifreeze
Technology	Silicate	OAT	Si-OAT	Hybrid	OAT	Silicate
BASF Code	G48	G30	G40	G05	N/A	N/A
VAG Code	G11	G12 & G12+	G12++ (also suitable for G13)	N/A	N/A	N/A
Service Life	3 year life	5 year life	5 Year Life	6,000 hour life	4 Years	2 Years

Passenger Vehicles	Audi upto 1996 (TL 774-C), BMW (N 600 690), Jaguar upto 1999 (VIN 878388), Maybach (MB 325.0), Mercedes Benz (MB 325.0), Mini (BMW N600 690), Mini Cooper D 07-10 – G30, Opel/Vauxhall upto 2000 (B 040 0240), Porsche upto 1995, Rolls Royce from 1998 (BMW N 600 690), Saab (690 1599), Seat upto 1996 (TL 774-C) Skoda upto 1996 (TL 774-C) Smart (MB 325.0), Tesla, VW upto 1996 (TL 774-C), Volvo Car, Zastava This product also protects: Chrysler Ferrari	Audi (TL 447-D/F), Bentley (TL 447-D/F), Bugatti (TL 447-D/F), Jaguar from 1999 (VIN 878389), Lamborghini (TL 447-D/F), Mini Cooper D (2007 - 2010), Porsche from 1996, Seat (TL 447-D/F), Skoda (TL 447-D/F) VW (TL 447-D/F) This product also protects: Chevrolet, Citroen, Honda, Hyundai, Kia, Land Rover Mazda, Mitsubishi, Nissan, Opel, Peugeot, Renault, Saab, Suzuki, Toyota, Vauxhall, Volvo Truck (as from 2006), Audi (TL 447-D/F), Bentley (TL 447-D/F), Bugatti (TL 447-D/F), Jaguar from 1999 (VIN 878389), Lamborghini (TL 447-D/F), Mini Cooper D (2007 - 2010), Porsche from 1996, Seat (TL 447-D/F), Skoda (TL 447-D/F), VW (TL 447-D/F).	Chrysler (MS-9769) Ford North America (WSS-M 97B51-A1)	Audi from 2005 (TL 447-G) Bentley from 2005 (TL 447-G) Bugatti from 2005 (TL 447-G) Lamborghini from 2005 (TL 447-G) Mercedes Cars (MB 325.6) Porsche from 1997, (911, Boxster, Cayman, Cayenne, Panamera) Seat from 2005 (TL 447-G), Skoda from 2005 (TL 447-G), VW from 2005 (TL 447-G)		
Commercial Vehicles	MAN (MAN 324 NF) MTU (MTL 5048) Deutz (H-LV 0161 0188) Jenbacher (Ta-Nr. 1000-0201) Liebherr (TLV 035, TLV 23009 A) Van Hool Volvo Truck upto 2005	DAF MTU (MTL 5048)	Cummins (CES 14603) MAN vehicles from 12/2011 (MAN 324 Si OAT) Mercedes Truck from 10/2011 (MB 325)	DAF MTU (MTL 5048)		
Fulfils the requirements of the following coolant standards:	AS 2108-2004, ASTM D 3306, ASTM D 4985, SAE J1034, AFNOR NFR 15-601, ÖNORM V 5123, CUNA NC 956-16, JIS K 2234:2006, SANS 1251:2005, SH 0521-1999, BS 6580:2010.	AS 2108-2004, ASTM D 3306, ASTM D 4985, BS 6580:2010, CUNA NC 956-16, AFNOR NFR 15-601, ÖNORM V 5123, SAE J1034, SANS 1251:2005, SH 0521-1999.	AS 2108-2004, ASTM D 3306, ASTM D 6210, BS 6580:2010, CUNA NC 956-16, AFNOR 15-601, SAE J1034, JIS K 2234:2006	AS 2108-2004, ASTM D 3306, ASTM D 4985, ASTM D 6210, SAE J1034, ÖNORM V 5123, CUNA NC 956-16, JIS K 2234:2006, SANS 1251:2005, SH 0521-1999, BS 6580:2010	DEF STAN 68-127, Nato Code 757, BS6580:2010	BS6580:2010