



PTFE Spray

Leaves non-stick dry film for applications between -40°C to $+150^{\circ}\text{C}$

Description

Synthetic lubricant aerosol for all types of industry.

Properties

PTFE Spray meets the FDA requirements of lubricants with incidental food contact, 21 CFR 178.3570 and is NSF H1 registered.

PTFE Spray doesn't contain animal derivatives and allergens listed in Annex II of Directive 2011/1169/EC on food ingredients.

PTFE Spray is formulated with a 100% synthetic base oil and specific additives ensuring high lubricating and anti-wear performance in a wide temperature range (-40°C to $+150/180^{\circ}\text{C}$, after evaporation).

The presence of PTFE type Teflon allows resistance to chemicals (alkalis, water washout, dust ...) and promotes long-term lubrication

After drying, PTFE Spray leaves a dry, non-stick and non-greasy film, limiting the risk of seizure of lubricated components and reduces friction.

PTFE Spray eliminates water in lubricated parts and protects against rust and corrosion.

Applications

PTFE Spray is recommended for the lubrication of machinery used in all types of industries, including manufacturing of food, beverages and packaging.

PTFE Spray is particularly recommended for the lubrication of slides, axles, chains, cams, columns, guides, skids, rails, conveyors, and various other mechanisms.

PTFE Spray is particularly recommended for lubrication in wet or dusty environments (flour, cardboard dusts, etc ...).

Specifications

	Unit	Value
Appearance	-	Liquid
Colour	-	White
Propellant gas	-	Butane/Propane
Volume	ml	500
NSF Registration	-	158901

Health/Safety

For information about safe handling and use of this product, refer to the Material Safety Data Sheet.

Storage & Handling

Caution pressurized container: protect from sunlight and other heat sources.

Use by Date

3 years after manufacture

Manufacture date can be identified from bottom of bottle as follows:

1. First 3 numbers indicate the day of the specific year (159 – means 159th day of the given year)
2. Letter to indicate production run on the day (A, B, C etc.)
3. Number to indicate filling line (between 1 and 5)
4. Last number for example 9 indicates the year – 2019

Note

The data contained in this publication is based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, this data does not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.



Terms & Conditions: © 2018. All rights reserved to Moove Lubricants Limited. Mobil and Mobil products named in this material are registered brands and trademarks of Exxon Mobil Corporation or one of its subsidiaries, licensed for use to Moove Lubricants Limited who are responsible for this document and the use of such trademarks within it. No part of this document or any trademark is permitted to be copied, reproduced or otherwise used or applied without prior consent.

Manufactured by Moove Lubricants Limited.
Operations Plant Dering Way, Gravesend, Kent DA12 2QX +44 (0) 1474 564 311